

# Evaluating *Reducing Risks in Type 1 Diabetes Using $H_\infty$ Control*

*Ravish Kumar (14542), Snehil Verma (14700), Sahil Vartak (14789)*

## 1. Introduction

The following results have derived from research paper titled *Reducing Risks in Type 1 Diabetes Using  $H_\infty$  Control* (*IEEE Transactions on Biomedical Engineering*, vol. 61, no. 12, December 2014) with the help of MATLAB R2016 application.

The class came across the paper when looking for learn application of Robust Control System in everyday life. The objective of the paper, as we have understood, is to automatically control the blood glucose level in T1DM patients which is a long standing problem and a constant threat to upcoming generation. While approaching the problem, we had two tools: Simulink and MATLAB. We chose the latter being well acquainted with the application. The following Matlab code is of the plant, *Adult#j* (as named in paper) and *gen\_plant* (named in code) depicting its bode plot which turns out to be similar to the papers result ensuring the meticulousness of our code. As there are millions of people from whole over the world so we cant model the plant for each individual. Hence, for more practicality of the scheme, paper designed a 3<sup>rd</sup> order plant model with only one tuning parameter known as a *priori* patient data. *TDL<sub>r</sub>* was taken to be 180, the average of general values found on surfing and similar goes to the other values. These values were assumed to meet the simplicity keeping care of practicality of the system. For the first part of submissions, we have derived the state space form of *K* for the plant, using *mixsyn* function. By using *ss2tf*, we have converted the state space form into transfer function. We used *sigma* function for getting the bode plots of sensitivity function and complementary sensitivity function. By assuming *SM=0* and *IFL=1*, our required function will be *T* as given in code and its curves are presented.




Figure 1. (a) Difference between healthy and affected cells (b) Effect of Hyperglycemia on blood cells

## 2. Understanding the Biological side of the problem

TYPE1 diabetes mellitus (*T1DM*) is caused when the body's immune system turns against itself and mistakenly attacks healthy cells. Thus it is classified as autoimmune disease and the healthy cells here are the the pancreatic  $\beta$ -cells which in turn causes deficiency of insulin. The huge problem to tackle in this disease is the self-monitoring of blood glucose throughout individual's life. We attempt to tackle this problem by achieving high closed-loop performance . People with type 1 diabetes always need to use insulin, but treatment can lead to low BG which is known as *hypoglycemia*.

*Hypoglycemia*, also known as low blood sugar, is when blood sugar decreases to below normal levels. Severe cases can lead to unconsciousness and are treated with intravenous glucose. *Hyperglycemia* is a condition in which an excessive amount of glucose circulates in the blood plasma. This is generally a blood sugar level higher than 11.1 mmol/l (200 mg/dl), but symptoms may not start to become noticeable until even higher values such as 1520 mmol/l (~250-300 mg/dl).

The UVA/Padova T1DMS is simulation software that ameliorates users to design and test treatment of in-silico subjects with Type 1 Diabetes Mellitus. The UVA/Padova T1DMS allows the user to perform experiments which examine and tune control algorithms for insulin dosing strategies and also guide and focus the emphasis of protocol designs for clinical studies.



Figure 2. Block diagram without IFL




Figure 3. Block diagram with IFL




Figure 4. Block diagram with Discrete filter w/o IFL

### 3. MATLAB Code

```

1  clc;
2  clear all;
3
4  % from the given dataset obtaining the value of IS_i
5  Avg_CF = 1;
6  Avg_CR = 1;
7  TDI_r = 180; % randomly choosed average value according to internet
8  Alpha = 0.5; % given avg value in paper
9  Beta = 0.5; % given avg value in paper
10 C_av = Alpha*Avg_CF + Beta*Avg_CR; %calculation of C_av for IS_i
11
12 TDI_i = 151; % Total daily insulin for random person saying Id_120
13 c = 1; % choosing for simplicity
14
15 IS_i = TDI_r * c / (TDI_i * C_av); % formula
16
17 Ts = 600; % sample time used 10min == 600 seconds
18
19 z = tf('z', Ts); % used for z-transform
20
21 % poles obtained from black_box method
22 p1 = 0.965;
23 p2 = 0.95;
24 p3 = 0.93;
25
26 c = 60/100*(1-p1)*(1-p2)*(1-p3)*Ts;
27 rj = 1800/TDI_i;
28 % writing general plant obtained from blackbox method
29 gen_plant = (c*rj*z^-3)/((1-(z^-1)*p1)*(1-(z^-1)*p2)*(1-(z^-1)*p3));
30

```

```

31 % bode(gen_plant); % uncomment for bode of gen_plant
32
33 % Hinfinity controller designing code
34
35 % weight on sensitivity matrix as given in paper
36 Wp = (0.01434*z - 0.01365)/(z - 0.9993);
37 % weight on k*sensitivity matrix as given n paper
38 Wdel_i = IS_i*1500*(0.001992*(z-1))/(z-0.992);
39 [Khinf,ghinf,GAM] = mixsyn(gen_plant, Wp,Wdel_i,[])
40 % Khinf will be in state space form and will give the desired controller
41
42 % this part of code is just to set the limits on Ms and Mt
43 L = gen_plant*Khinf; % open loop transfer function.
44 S = inv(1+L); % defining sensitivity function
45 T = L*S; % defining complementary sensitivity function
46
47 % To plot the following output
48
49 sigma(S, 'g',T, 'r',GAM/Wp, 'g-',GAM*gen_plant/ss(Wdel_i), 'r-');
50 legend('S', 'T', 'GAM/Wp', 'GAM*gen_plant/ss(Wdel_i)', 'Location', 'Northeast');
51
52 % obtaining the controller from state space form
53 [b, a] = ss2tf(Khinf.A, Khinf.B, Khinf.C, Khinf.D);
54 % a and b will be used in determining the controller in z-transform
55
56 Zcon = ss(Khinf); % controller in z-transformed form
57 zpk(Zcon); % factorising Z_controller
58 rZcon = balred(Zcon,3); % reduced Z_controller into order 3
59 zpk(rZcon) % factorising reduced Z_controller
60
61 % obtaining step response of closed loop system (uncomment next line)
62 % step(gen_plant*Khinf/(1+gen_plant*Khinf));
63
64 % To get a feel of gain margin & phase margin of open loop TF from r to g
65
66 Marg = allmargin(gen_plant * Khinf);
67
68 % Khinf will be found from the mixsyn function in the discrete time domain
69 % but in state-space form. In z transform we have to use ss2tf function
70 % that will give b and a as follows:
71
72 % b = [0.0007 -0.0019 0.0011 0.0014 -0.0018 0.0006]
73 % a = [1.0000 -4.2934 7.3537 -6.2774 2.6677 -0.4505]
74
75 % using this we can write the controller in z-transformed form as follows:
76
77 % 0.00067949 (z+1.002) (z-0.992) (z-0.965) (z-0.95) (z-0.93)
78 % -----
79 % (z-0.6034) (z-0.992) (z-0.9993) (z^2 - 1.699z + 0.7532)
80
81 % 3rd order reduced controller in z-transformed form:
82
83 % 0.00084182 (z+0.1629) (z^2 - 1.952z + 0.9527)
84 % -----
85 % (z-0.9993) (z^2 - 1.626z + 0.7324)
86
87 % results of Marg function are

```

```

88
89 % GainMargin : [5.1585 2.2600e+04]
90 % GMFrequency: [2.8741e-04 0.0037]
91 % PhaseMargin: 75.7700
92 % PMFrequency: 5.5464e-05
93 % DelayMargin: 39.7389
94 % DMFrequency: 5.5464e-05
95 % Stable: 1
96
97 % Insulin feedback loop
98 % Designing SIM
99 % Defining parameters
100 kd = 0.0164/60;
101 ka1 = 0.0018/60;
102 ka2 = 0.0182/60;
103 m1 = 0.19/60;
104 m2 = 0.484/60;
105 m3 = 0.285/60;
106 m4 = 0.194/60;
107 Vi = 0.05;
108 mu = 7.5;
109
110 A = [-(kd+ka1) , 0 , 0 , 0 ; kd , -ka2 , 0 , 0 ; 0 , 0 , -(m1+m3) , m2 ; ka1 , ka2 , m1 , -(m2+m4) ];
111 B = [ 1 ; 0 ; 0 ; 0 ];
112 C = [ 0 0 0 1/Vi ];
113 D = 0;
114
115 sys = ss(A,B,C,D);
116 % function used for conversion of continuos TF to discrete TF
117 opt = c2dOptions('Method','tustin','FractDelayApproxOrder',3);
118 sysd1 = c2d(sys,600,opt) % SIM == sysd1
119 % IFL = 1/(1+mu*SIM);

```

#### 4. Project development and experience

- First of all we were unaware that Control Systems can be used in biological aspects too. So we learnt that this is also an area of research where control engineers can make their remarkable contributions.
- We learnt Simulink for simulation of our plant model, to observe the working of controllers and their behaviour on encountering disturbance in insulin levels.
- We learnt variety of new commands used in the MATLAB and Octave, especially used in robust control like ss2tf, balred, sigma, mixsyn, marg and zpk.
- We learnt black box method i.e. finding a plant model of unknown system by techniques as discussed in the class.
- We saw experimentally the effects on performance and control effort of the controller due to change in weights which supported the theory and clarified the concepts.
- We learnt discrete-time domain representation of transfer function. For this we skimmed through bilinear transformation, Z-transformation and relation between Z-plane and S-plane.
- Nyquist frequency bounds :- The choice of sampling time depends on nyquist frequency. Calculated maximum allowed sampling time was 52 mins for our plant and we assumed it to be 10 mins which is feasible.
- We learnt the reason behind the non-existing nature of bode plot after certain frequency i.e.  $\pi/Ts = 0.5e-3$  rad/s.
- At first we got controller as a  $5^{th}$  order transfer function but since it was unfeasible in terms of order, so we reduced the order of controller to  $3^{rd}$  order.

5. Plots




Figure 5. Bode plot of gen\_plant




Figure 6. Bode plot of different functions via sigma()




Figure 7. Step response of closed loop transfer function




Figure 8. Root locus of controller  $K h_{inf}$  in  $Z_{plane}$




Figure 9. Root locus of gen\_plant in  $Z_{plane}$




Figure 10. Root locus of gen\_plant\* $K h_{inf}$  in  $Z_{plane}$




Figure 11. Comparison between close loop performances of block diagram with and without IFL




Figure 12. Showing  $e_{s,s}$  in IFL is very low




Figure 13. Disturbance with and without IFL

## 6. Problems faced

- Paper was not written in an efficient manner i.e. there was lack of some useful information regarding terms used in the paper such as it didn't show the presence of basal insulin which we need to add before giving input to Adult#j.
- We were first unaware of discrete time domain transfer function which cost us time.
- Safety Mechanism is still not clear to us, so we dropped safety mechanism from our simulation.
- The use of IFL is still questionable as IFL just reduced the steady state error while overshoot and settling time became worse as compared to the one without IFL block simulation.
- Settling time for disturbances is very high i.e. 4 to 5 hour, which we think is very high and inappropriate.

## 7. Results

- The bode plot of the open loop transfer function stopped at the frequency  $\pi/T_s$  which is approximately  $0.5e-3$ .
- Basal insulin level for our plant is  $0.091019$  mg/dl, which we tuned from the simulation.
- Settling time of CL response was 4 to 5 hours.
- From the root locus plots of the plant model, controller and plant\*controller we can decide their stabilities.
- To make sure that the input to the plant Adult#j is always non-negative we increased the weight on  $W_{del}$ . We increased the constant (given in paper) by a factor of 1500.
- IFL reduced the steady state error while overshoot and settling time became worse as compared to the one without IFL block simulation.
- After tuning the constants of discrete filter it seemed that the two curves (with or without filter) were overlapping each other but the filter smoothed the response.

## 8. Contributions in brief

**Snehil Verma:** Basic Programming, designing Insulin Feedback Loop (IFL), reduced order model of the controller, Simulink simulation, L<sup>A</sup>T<sub>E</sub>X presentation and documentation

**Ravish Kumar:** Basic Programming, brief explanation of paper to own group, weight optimization, designing Insulin Feedback Loop (IFL), Simulink block diagram designing and simulation, discrete filter design, documentation

**Sahil Varthak:** Basic Programming, Simulink simulation, collection of general information for documentation

## Acknowledgement

We have taken efforts in this project. However, it would not have been possible without the kind support of many individuals and organisations. We would like to extend my sincere thanks to all of them. We are highly indebted to Prof. Ramprasad Potluri for his guidance, constant supervision as well as providing invaluable information about the project and supporting in completing the project. This effort would be of huge waste without thanking the developers of MATLAB which was a very necessary tool in completion of work. We would also like to express special gratitude to the writers of paper and making it available to anyone willing to work on it. Our thanks and appreciation go to our talented colleagues who were willing to help each other to best of their abilities.

## References

1. IEEE Transactions on Biomedical Engineering, vol. 61, no. 12, December 2014 *Reducing Risks in Type 1 Diabetes Using  $H_\infty$  Control*.
2. ss2tf function <https://in.mathworks.com/help/matlab/ref/ss2tf.html>.
3. Bilinear transformation [https://en.wikipedia.org/wiki/Bilinear\\_transform](https://en.wikipedia.org/wiki/Bilinear_transform).
4. Sigma function <https://in.mathworks.com/help/robust/ref/mixsyn.html?requestedDomain=in.mathworks.com>.
5. Figure 1(a) [https://thumb9.shutterstock.com/display\\_pic\\_with\\_logo/636694/212467696/stock-vector-type-diabetes-labeled-diagram-212467696.jpg](https://thumb9.shutterstock.com/display_pic_with_logo/636694/212467696/stock-vector-type-diabetes-labeled-diagram-212467696.jpg).
6. Figure 1(b) <http://elbrooklyntaco.com/wp-content/uploads/2013/10/hyperglycemia.jpg>.
7. Model order reduction <https://www.mathworks.com/help/control/ref/balred.html>.
8. Control system toolbox functions <http://www.mathworks.com/help/control/functionlist.html>.